

蒸汽清洗机JNX-G24
Steam Washer JNX-G24

规格specification		图片
货号Model	JNX-G24	
蒸汽压力 Steam pressure	20-25BAR	
流量Flow	108-120L/H	
蒸汽温度 Steam temperature	179° -191°	
电压Voltage	380V/50Hz	
电机Motor	0.75KW 1450	
发热体功率 Heating body power	24KW	
水箱Tank capacity	18L	
产汽时间 Steam production time	60S	
尺寸Size	1260X560X690mm	
标准配置standard configuration		功能特点
1. 10米钢丝编织四氟蒸汽管 10 m steel wire braided teflon steam pipe	1. 防爆技术和防爆控制箱 Explosion-proof technology and explosion-proof control box	
2. 工业级蒸汽枪 Industrial grade steam gun	2. 蒸汽干湿度自由调节 Steam dry humidity free regulation	
3. 蒸汽喷嘴 steam nozzle	3. 中央净化水过滤器; Central water filter;	
4. 去油污刷头 Remove grease brush head	4. 意大利进口AR水泵 Italy imported AR water pump	
5. 长枪杆 Long gun rod	5. 防震实心轮胎 Shock proof solid tire	
6. 机器机身304不锈钢板 Machine body is 304 stainless steel plate	6. 进口接触器等进口配件 Imported contactor and other imported accessories	

蒸汽清洗机JNX-G36
Steam Washer JNX-G36

规格specification		图片
货号Model	JNX-G36	
流量Flow	100-200L/h	
功率Power	36KW	
电机Motor	0.75KW 1450	
电压Voltage	380V/50Hz	
加热类型Type of heating	即热式 instant	
水箱容量Tank capacity	18L	
冷机启动时间 Chillers start time	60S	
水泵water pump	意大利AR Italy AR	
蒸汽压力steam pressure	20-30BAR	
温度temperature	175-230°	
尺寸Size	1260X560X690mm	
标准配置standard configuration		功能特点
1. 工业级高压蒸汽枪 Industrial high pressure steam gun		1. 防爆技术和防爆控制箱 Explosion-proof technology and explosion-proof control box
2. 圆心高压喷嘴 Centered high pressure nozzle		2. PLC控制系统 PLC controlling system
3. 10米钢丝编织四氟蒸汽管 10 m steel wire braided teflon steam pipe		3. 精密压力控制器 Precision pressure controller
4. 机器机身为304不锈钢板 Machine body is 304 stainless steel plate		4. 数字温度控制系统 Digital temperature control system
5. 去油污刷头 Remove grease brush head		5. 变频水泵调节 Variable frequency pump regulation
6. 长枪杆 Long gun rod		6. 缺水报警保护系统 Water shortage alarm protection system
7. 易损配件扳手工具等 Fragile accessories wrench tools, etc		7. 过热保护系统 Overheat protection system
		8. 过压保护系统 Overvoltage protection system